



INTEGRATED THERMOELECTRIC MODULE

Technical field

The present invention generally refers to the field of solid-state
5 thermoelectric devices using the Peltier effect to cool and/or heat civil
and/or industrial environments.

Prior art

The thermoelectric devices of the abovementioned type have
been known in the art for quite some time and generally comprise a
10 thermoelectric module or thermopile consisting of a set of
thermoelectric elements which, in their turn, are formed by P type
and N type conductor and/or semiconductor elements electrically
connected in series and thermally connected in parallel, wherein the
thermoelectric elements are usually electrically connected in series
15 and thermally connected in parallel and are assembled on supports
made of electrically insulating, but thermally conductive, material
and generally made of stiff ceramic material. These thermoelectric
modules must then be connected to heat exchangers in order to form
heat pumps for household and industrial appliances.

20 The thermoelectric modules known in the art generally present
some drawbacks related to their thermal efficiency and fragility. As to
the first of these drawbacks, in particular, the thermoelectric modules
known in the art ~~do~~are ~~not~~ allow ~~able~~ to achieve a uniform
temperature distribution on the heat exchangers to which they are
25 connected, because they cannot be adapted to the variable

characteristics of the heat exchangers depending on the type of application they are intended for. As to the second drawback, it is known that, because of the fragility of the support, during the assembly steps with the heat exchangers ruptures frequently occur
5 due to the high contact pressures required for good functioning and/or during operation due to the different thermal expansions of the two faces of the module, caused by the different temperatures of the heat exchangers they are connected to.

Disclosure Summary of the invention

10 The present invention pursues the object to overcome ~~said-the~~ above-mentioned drawbacks of the thermoelectric modules known in the art by providing a newly designed thermoelectric module that is to be assembled and integrated with heat exchangers in order to form a thermoelectric heat pump.

15 According to the present invention, this object is achieved by a an integrated thermoelectric module formed of a set of thermoelectric elements, each of which is made of P type and N type conductor and/or semiconductor elements electrically connected in series and thermally connected in parallel, wherein ~~said-the~~ thermoelectric
20 elements are electrically connected in series and/or in parallel and thermally connected in parallel and are assembled on flexible supports made of a polymeric material capable of electrically insulating the circuit, but having a high thermal conductivity performance. ~~Said-These~~ supports, one being on the hot side and
25 the other on the cold side of the thermoelectric module, are

connected to their respective heat exchangers by means of connecting materials having low thermal impedance, for instance of phase conversion type or graphite-base type, allowing optimum connection even at low adhesion pressures. ~~Said~~The integrated
5 module is characterized in that the thermoelectric elements are distributed in its interior so as to geometrically harmonize heat transferred from the integrated thermoelectric module with heat exchanged by the heat exchangers, thus making the temperature distribution on ~~said~~the heat exchangers as uniform as possible, in
10 order to maximize the efficiency of the integrated thermoelectric module by reducing the thermal head between its two faces.

Brief description of the drawings

The present invention will now be described as a non-limiting example with reference to the figures of the accompanying drawings,
15 in which:

figure 1 is a sectional view of the integrated thermoelectric module according to the invention, associated with heat exchangers of planar form in order to form a thermoelectric heat pump;

figure 2 is a sectional view of the integrated thermoelectric
20 module according to the invention, associated with heat exchangers of concave and/or convex form in order to form a thermoelectric heat pump;

figure 3 is a sectional view of the integrated thermoelectric module according to the invention, associated with heat exchangers

of cylindrical form with a polygonal cross section in order to form a thermoelectric heat pump; and

figure 4 is a sectional view of the integrated thermoelectric module according to the invention, associated with heat exchangers
5 of cylindrical form with circular cross section in order to form a thermoelectric heat pump.

Best mode of carrying out the Detailed description of the invention

Referring to figure 1 of the drawings, the integrated
10 thermoelectric module 10 is formed of a set of thermoelectric elements, as described above, assembled on flexible supports 11 having the form of a thin membrane or film of polymeric material. The thermoelectric elements are uniformly or non-uniformly distributed on the flexible support 11 depending on the particular use the
15 thermoelectric module 10 is intended for.

The peripheral shape of the integrated thermoelectric module may be different and may be rectangular, for instance even square, or curvilinear, for instance circular.

The polymeric material of the flexible support 11 is preferably
20 made of a polyimide, commercially available under the trade name Kapton®.

The integrated thermoelectric module 10, thus formed, is associated with heat exchangers 12 and is caused to adhere to the base surfaces of the latter, preferably by means of a thermo
25 conductive material 13 of phase conversion type. Instead of the

thermo conductive material of phase conversion type, a graphite material may be used as connecting material, laid on one side only or on both sides of the integrated thermoelectric module 10.

5 The base surfaces of the heat exchangers may be planar, as shown in figure 1, or concave and/or convex, as shown in figure 2, or cylindrical with a polygonal cross section, as shown in figure 3, or cylindrical with circular cross section, as shown in figure 4. Heat exchangers 12 may be touched by gaseous or liquid fluids as well as by fluids undergoing phase conversion. In addition, the surfaces
10 being touched may be provided with fins. The heat exchangers 12 may be made of metal or non-metal material. For instance, as non-metal material, a graphite material may be used.

The connecting materials used to connect the integrated thermoelectric module 10 to the heat exchangers 12 may be either
15 distributed in a substantially uniform way on the flexible support 11 or they may be localized on the flexible support 11 in correspondence with the thermoelectric elements.

The technical advantages achieved with a thermoelectric device according to the invention are as follows.

20 With a proper distribution of the thermoelectric elements inside the integrated thermoelectric module 10, it is possible to harmonize the configuration of ~~said the~~ module with that of the heat exchangers 12 in order to improve the correspondence between heat transferred from the module and heat exchanged by the heat exchangers 12 and
25 to achieve a temperature distribution as uniform as possible, thus

improving efficiency of the integrated thermoelectric module 10 with reduction of the thermal head between its two faces.

Industrial applicability

5 The use of a connecting material between integrated thermoelectric module 10 and heat exchangers 12, as described, permits to obtain a stable connection even in the absence of an excessive contact pressure in order to achieve close contact between the integrated thermoelectric module and heat exchangers. In addition, ~~said~~ the connecting materials have high thermal
10 conductivity and are capable of absorbing, in the best possible manner and without ~~damages~~ damage to the module itself, possible thickness irregularities of the module due to different height of the thermoelectric elements and differential effects in terms of thermal expansion of the heat exchangers, when, during operation, they find
15 themselves at mutually different temperatures. Finally, if heat exchangers are used having non-planar adhesion surfaces, ~~said~~ the connecting materials could be used to offset non-conformity of the planar base of the thermoelectric elements with the curvature of the exchanger base, by filling up the interstices that are present between
20 flexible support 11 and surface of heat exchangers 12.

INTEGRATED THERMOELECTRIC MODULE

ABSTRACT

5

The—An integrated thermoelectric module is formed of a set of thermoelectric elements, consisting of N type and P type conductor and/or semiconductor elements electrically connected in series and thermally connected in parallel, the thermoelectric elements being
10 electrically connected in series and/or in parallel and thermally connected in parallel and being assembled on flexible supports of polymeric material, capable of electrically isolating said circuit, but having a high thermal conductivity efficiency. Each support is connected to a heat exchanger by means of connection materials
15 having low thermal impedance allowing optimum connection even at low adhesion pressures. The thermoelectric elements are distributed in its interior part so as to geometrically harmonize heat transferred from the integrated thermoelectric module with heat exchanged by the heat exchangers, thus making the temperature distribution on
20 said heat exchangers as uniform as possible, in order to maximize the efficiency of the integrated thermoelectric module.